



Standard Features on Duraline Motors

- ✓ Totally Enclosed Fan Cooled Motors (TEFC)
- ✓ Stainless steel name plate
- ✓ Rubber v-ring shaft slingers
- ✓ Class F insulation
- ✓ Nema Design A for all 4 pole motors from 10 to 50HP
- ✓ Nema Design B for all motors above 50HP
- ✓ Available in 208/230-460V and 575 60Hz
- ✓ Available in 380V 50Hz
- ✓ Service Factor 1.15
- ✓ Cast iron frame, feet and junction box
- ✓ NPT threaded outlets on terminal boxes
- ✓ Dual mounting feet for increased versatility
- ✓ Sealed bearings on 143T-215T frames
- ✓ Regreasable bearings from 254T to 586/7T frames
- ✓ Roller Bearings standard on 100HP motors and larger
- ✓ Use only brand name bearings
- ✓ Star delta start from 284T frame and up
- ✓ Dynamically balanced die cast aluminum rotor
- ✓ F1 & F2 field reversible
- ✓ High efficiency motors meet and exceed CSA390 and epact requirements
- ✓ 4140f high tensile steel on 449T frames and larger
- ✓ C & D Flanges available
- ✓ Factory approved 4:1 turndown rating
- ✓ Continuous Duty rating